

BIBLIOGRAFIA

- Akaike H. (1974), A new look at statistical model identification, *IEEE Trans. Autom. Control*, AC-19, 716–722.
- APAT, Operative plan for the implementation of I&CLC2000 project in Italy. 25 Novembre 2002.
- Beretta G.P., Francani V., Fumagalli L. (1992), *Studio Idrogeologico della Provincia di Cremona*, Pitagora Editrice Bologna.
- Bozdogan H. (1987), Model selection and Akaike's information criterion (AIC): The general theory and its analytical expansions, *Psychometrika*, 52(3), 345-370.
- Capilla J. E., Gomez-Hernandez J. J., Sahuquillo A. (1997), Stochastic simulation of transmissivity fields conditional to both transmissivity and piezometric data, 2, Demonstration on a synthetic aquifer, *J. Hydrol.*, 203, 175-188.
- Carle S.F., Fogg G.E. (1996), Transition probability-based indicator geostatistics, *Math Geol*, 28(4), 453-476.
- Carrera J. (1993), An overview of uncertainties in modelling groundwater solute transport, *Journal of Contaminant Hydrology*, 13, 23-48.
- Carrera J., Alcolea A., Medina A., Hidalgo J., Slooten L. J., (2005), Inverse problem in hydrogeology, *J. Hydrol.*, 13, 206-222.
- Carrera, J., and S. P. Neuman (1986a), Estimation of aquifer parameters under transient and steady state conditions: 1. Maximum likelihood method incorporating prior information, *Water Resour. Res.*, 22(2), 199–210.
- Carrera, J., and S. P. Neuman (1986b), Estimation of aquifer parameters under transient and steady state conditions: 3. Application to synthetic and field data, *Water Resour. Res.*, 22(2), 228–242.
- Cavanaugh J. E., and Neath A. A. (1999), Generalizing the derivation of the Schwarz information criterion, *Commun. Stat. Theory Methods*, 28, 49-66.
- Dagan G. (1985), Stochastic modeling of groundwater flow by unconditional and conditional probabilities: The inverse problem, *Water Resour. Res.*, 21(1), 65-72.
- Dagan G., Rubin Y. (1988), Stochastic identification of recharge, transmissivity and storativity in aquifer transient flow: A quasi-steady approach, *Water Resour. Res.*, 24(10), 1698-1710
- de Marsily G., Delay F., Gonçalves J., Renard P., Teles V., Violette S. (2005), Dealing with spatial heterogeneity, *J. Hydrol.*, 13, 161-183.
- Deutsch C. V., Journel A.G. (1998), *GSLIB: Geostatistical Software Library and User's Guide*, Oxford University Press, New York, pages 340.
- Dietrich, C. R., Newsam G. N. (1990), Sufficient conditions for identifying transmissivity in a confined aquifer, *Inverse Prob.*, 6(3), 21-28.
- Doherty, J. (2006), *PEST Model-Independent Parameter Estimation*, V10.1, Papadopoulos. S. S., Inc., Bethesda, Md.
- Doherty J., Brebber L., Whyte P. (2002), *PEST-Modelling dependent parameter estimation*, Water Mark Computing, Corinda (Australia).
- Draper D. (1995), Assessment and propagation of model uncertainty, *J. Roy. Statist. Soc. Ser., B* 57, 45-97.
- European Environmental Agency - European Topic Center-Terrestrial Environment, CORINE land cover up-date. I&CLC2000 project. Technical Guidelines. European Environmental Agency, 2002.
- Fisher R. A. (1922), On the mathematical foundations of theoretical statistics, *Philos. Trans. R. Soc., Ser. A.*, 222, 309–368.
- Regione Lombardia, ENI - Agip, (2001), *Geologia degli acquiferi padani della Regione Lombardia*. A cura di Cipriano Carcano e Andrea Piccin. S.EL.CA. (Firenze).
- Gomez-Hernandez J. J., Complexity (2006), *Ground Water*, 44 (6), 782-785.

- Gomez-Hernandez J. J., Sahuquillo A., Capilla J. E. (1997), Stochastic simulation of transmissivity fields conditional to both transmissivity and piezometric data, 1, Theory, J. Hydrol., 203, 162-174.
- Gonzalez R. V., Giudici M., Ponzini G., Parravicini G. (1997), The differential system method for the identification of transmissivity and storativity, Transp. Porous Media, 26, 339-371.
- Grindrod P., Impey M. D. (1991), Fractal field simulations of tracer migration within the WIPP Cullebra Dolomite, Internat. J. Technol., Henley-upon-Thames, U. K., Dec.
- Guadagnini, L., A. Guadagnini, and D.M. Tartakovsky (2004), Probabilistic Reconstruction of geologic facies, J. of Hydrol., 294, 57-67.
- Gutjahr A., Bullard B., Hatch S., Hughson L. (1994), Joint conditional simulations and the spectral method approach for flow modeling, Stochastic Hydrol. Hydraul., 8(1), 79-108.
- Gutjahr A. L., Wilson J. R. (1989), Co-kriging for stochastic flow models, Transp. Porous Media, 4(6), 585-598.
- Hill M. C. (1998), Methods and guidelines for effective model calibration, U.S. Geol. Surv. Water Resour. Invest. Rep., 98-4005, 90 pp.
- Hill M. C., Banta E. R., Harbaugh A. W., Anderson E. R. (2000), MODFLOW-2000, the U. S. Geological Survey modular groundwater model—User guide to the observation, sensitivity, and parameter estimation processes and three post-processing programs, U.S. Geol. Surv. Open File Rep., 00-184, 209 pp.
- Hoeksema R. J., Kitanidis P.K. (1984), An application of the geostatistical approach to the inverse problem in two-dimensional groundwater modeling, Water Resour. Res., 20(7), 1003-1020.
- Hoeting J.A., Madigan D., Raftery A.E., Volinsky C.T. (1999), Bayesian model averaging: A tutorial, Statist. Sci., 14(4), 382-417.
- Hubbard S., Rubin Y. (2000), A review of selected estimation techniques using geophysical data, J. Contamin. Hydrol., 45, 3-34.
- Hurvich, C. M., and C.-L. Tsai (1989), Regression and time series model selection in small sample, Biometrika, 76(2), 99–104.
- Kashyap, R. L. (1982), Optimal choice of AR and MA parts in autoregressive moving average models, IEEE Trans. Pattern Anal. Mach. Intel., 4(2), 99– 104.
- Kitadinis P. K., Introduction to Geostatistics: Application in Hydrogeology, (1996), Cambridge University Press, Cambridge.
- Kitanidis P. K., Lane R. W. (1985), Maximum likelihood parameter estimation of hydrologic spatial processes by the Gauss-Newton method, Hydrol., 79(1-2), 53-71.
- Kitanidis, P. K., Vomvoris E. G. (1983), A geostatistical approach to the inverse problem in groundwater modeling (steady state) and one dimensional simulations, Water. Resour. Res., 19(3), 677-690.
- Isaaks E. H., Srivastava R. M., An Introduction to Applied Geostatistics, Oxford University Press (1989), New York, p.561.
- Journel A.G. (1983), Nonparametric estimation of spatial distribution, Math. Geol., 15(3), 445-468
- Journel A.G., Alabert F.G. (1990), New method for reservoir mapping, J. Pet. Technol. February, 42(2), 212-218.
- Journel A.G., Gomez-Hernandez J. (1993), Stochastic imaging of the Wilmington clastic sequence, Soc. Pet. Eng. Form. Eval. March, 8(1), 33-40.
- Journel A.G., Isaaks E.K. (1984), Conditional indicator simulation: application to a Saskatchewan uranium deposit, Math Geol., 16(7), 685-718.
- Koltermann C.E., Gorelick S.M. (1992), Paleoclimatic signature in terrestrial flood deposits, Science, 256, 1775-1782.
- Lavenue M.A., de Marsily G. (2001), Three-dimensional interference test interpretation in a fractured/unfractured aquifer using the pilot point inverse method, Water. Resour. Res., 37(11), 2659-2675.

- LaVenue A.M., RamaRao B. S., de Marsily G., Marietta M.G. (1995), Pilot point methodology for automated calibration of an ensemble of conditionally simulated transmissivity fields, *Application, Water Resour. Res.*, 31(3), 495-516.
- LeBlanc D. R., Garabedian S. P., Hess K. M., Gelhar L. W., Quadri R. D., Stollenwerk K. G., Wood W. W. (1986), Large-scale natural gradient tracer test in sand and gravel, Cape Cod, Massachusetts: 1. Experimental design and observed tracer movement, *Water Resource Research*, 27 (5), 895-910
- Linhart H., and Zucchini W. (1986), *Model Selection*, John Wiley, Hoboken, N. J.
- Liu C. W., Jang C. S., Liao C. M. (2004), Evaluation of arsenic contamination potential using indicator kriging in the Yun-Lin aquifer (Taiwan), *Science of the Total Environment*, 321, 173–188.
- Mackay D.M., Freyberg D.L., Roberts P.V., Cherry J.A. (1986), A natural gradient experiment on solute transport in a sand aquifer : 1. Approach and overview of plume movement, *Water Resource Research*, 22 (13), 2017-2029.
- Madigan D., Raftery A.E. (1994), Model selection and accounting for model uncertainty in graphical models using Occam's window, *J. Amer. Statist. Assoc.*, 89, 1535-1546.
- Maione, U., and A. Paoletti, G. Ghezzi (1991), Studio di gestione coordinata delle acque di superficie e di falda nel territorio compreso fra i fiumi Adda e Oglio e delimitato dalle Prealpi e dalla linea settentrionale di affioramento dei fontanili.
- Matheron G., Beucher H., de Fouquet C., Galli A., Guerillot D., Ravenne C. (1987), Conditional simulation of the geometry of fluvio-deltaic reservoirs, *Society of Petroleum Engineers SPE* 16753.
- McDonald M. G., A. W. Harbaugh (1988), A modular three-dimensional finite-difference groundwater flow model, Manual 83-875. U.S. Geological Survey.
- Neuman S.P. (1973), Calibration of distributed parameter groundwater flow models viewed as a multiple-objective decision process under uncertainty, *Water Resour. Res.*, 9(4), 1006-1021.
- Neuman S. P. (2003), , Maximum likelihood Bayesian averaging of uncertain model predictions, *Stochastic Environmental Research and Risk Assessment*, 17, 291–305.
- Neuman S. P., Mishra P. K., Pumping test of unsaturated aquifer constitutive models, parameters and uncertainties, Department of Hydrology and Water Resources, University of Arizona.
- Pollock D. W. (1994), "User's guide for MODPATH/MODPATH-PLOT, version 3: A particle tracking postprocessing package for MODFLOW: the U.S. Geological Survey finite-difference ground-water flow model." U.S. Geological Survey, Open-File Rep. No. 94-464, Washington, D.C.
- Programma di Tutela e Uso delle Acque, L. R. 12/12/03 n. 26, art. 45, comma 3; D.Lgs. 11/05/99, n. 152, art. 44, Titolo IV, Capo I, definitivamente approvato con Delibera di Giunta n. 2244 del 29 marzo 2006.
- Provincia di Cremona: www.atlanteambientale.it
- Raftery A.E. (1993), Bayesian model selection in structural equation models, In: *Testing Structural Equation Models* Bollen K, Long J (eds.), pp. 163-180. Sage, Newbury Park, California.
- RamaRao B. S., LaVenue A. M., de Marsily G., Marietta M. G. (1995), Pilot point methodology for automated calibration of an ensemble of conditionally simulated transmissivity fields,1 , *Theory and computational experiments, Water Resour. Res.*, 31(3), 475-493.
- Rametta, D. (2008), Interazione tra reticolo idrografico superficiale e acquifero sotterraneo nella modellistica idrologica distribuita, Politecnico di Milano, Milano.
- Raoult Y. (1999), La nappe de l'Albien dans le bassin de Paris: de nouvelles id_ es pour de vieilles eaux (The Albien aquifer in the Paris basin: new ideas for old waters), Doctoral thesis, University Pierre et Marie Curie, Paris VI, 170 pp.
- Regione Lombardia: www.cartografia.regione.lombardia.it
- Ritzi R. W., Jayne D. F., Zahradnik A. J., Field A. A., Fogg G. E. (1994), Geostatistical Modeling of Heterogeneity in Glaciofluvial, Buried-Valley Aquifers, *Groun Water*, 32(4), 666-674.

- Rubin Y. (1991a), Prediction of tracer plume migration in disordered porous media by the method of conditional probabilities, *Water Resour. Res.*, 27(6), 1291-1308.
- Rubin Y. (1991b), Transport in heterogeneous porous media: Prediction and uncertainty, *Water Resour. Res.*, 27(7), 1723-1738.
- Rubin Y., Dagan G. (1987), Stochastic identification of transmissivity and effective recharge in steady groundwater flow, 1, Theory, *Water Resour. Res.*, 23(7), 1185-1192.
- Sahuquillo A., Capilla J. E., J. J. Gomez-Hernandez, Andreu J. (1992), Conditional simulation of transmissivity fields honoring piezometric data, in *Hydraulic Engineering Software IV, Fluid Flow Modeling*, vol. 2, edited by Blain and Cabrera, pp. 201-214, Elsevier Sci., New York.
- Salamon P., Fernández-García D., Gomez-Hernandez J.J. (2007), Modeling tracer transport at the MADE site: The importance of heterogeneity, *Water Resour. Res.*, 40 W08404 doi: 10.1029/2006WR005522.
- Samper, F. J., and S. P. Neuman (1989), Estimation of spatial covariance structures by adjoint state maximum likelihood cross validation: 1, Theory, *Water Resour. Res.*, 25(3), 351–362.
- Samper, F. J., and S. P. Neuman (1989), Estimation of spatial covariance structures by adjoint state maximum likelihood cross validation: 2, Synthetic experiments, *Water Resour. Res.*, 25(3), 363–371.
- Samper, F. J., and S. P. Neuman (1989), Estimation of spatial covariance structures by adjoint state maximum likelihood cross validation: 3, Application to Hydrochemical and Isotopic Data, *Water Resour. Res.*, 25(3), 373–384.
- Schwarz, G. (1978), Estimating the dimension of a model, *Ann. Stat.*, 6(2), 461–464.
- Stallman R.W. (1956), Numerical analysis of regional water levels to define aquifer hydrology, *Am Geophys Union Trans*, 37(4), 451-460.
- Stauffer F., Guadagnini A., Butler A., Franssen H. H., Van de Wiel N., Bakr M., Riva M., Guadagnini L. (2005), Delineation of Source Protection Zones Using Statistical Methods, *Water Resour. Man.*, 19, 163-185.
- Studio di gestione coordinata delle acque di superficie e di falda nel territorio compreso fra i fiumi Adda e Oglio e delimitato dalle Prealpi e dalla linea settentrionale di affioramento dei fontanili, U. Maione, A. Paoletti, G. Grezzi, 1991.
- Studio idrogeologico della Provincia di Cremona, Beretta G.P., Francani V., Fumagalli L., 1992, Pitagora Editrice Bologna.
- Tsai F., Li X. (2008), Inverse groundwater modeling for hydraulic conductivity estimation using Bayesian model averaging and variance window, *Water Resour. Res.*, 44, W09434, doi:10.1029/2007WR006576.
- Ye M., Neuman S. P., Meyer P. D. (2004), Maximum likelihood Bayesian averaging of spatial variability models in unsaturated fractured tuff, *Water Resour. Res.*, 40, W05113, doi:10.1029/2003WR002557.
- Ye M., Neuman S. P., Meyer P. D. (2008), On model selection criteria in multimodel analysis, *Water Resour. Res.*, 44, W03428, doi:10.1029/2008WR006803.
- Ye M., Neuman S. P., Meyer P. D., Pohlmann K. (2005), Sensitivity analysis and assessment of prior model probabilities in MLBMA with application to unsaturated fractured tuff, *Water Resour. Res.*, 41, W12429, doi:10.1029/2005WR004260.
- Zimmerman D. A., de Marsily G., Gotway C. A., Marietta M. G., Axness C. L., Beauheim R. L., Bras R., Carrera J., Dagan G., Davies P. B., Gallegos D. P., Galli A., Gomez-Hernandez J., Gorelick S. M., Grindrod P., Gutjahr A. L., Kitanidis P. K., Lavenue A. M., McLaughlin D., Neuman S. P., RamaRao B. S., Ravenne C., Rubin Y. (1998), A comparison of seven geostatistically-based inverse approaches to estimate transmissivities for modeling advective transport by groundwater flow. *Water Resour. Res.* 34(6): 1373–1413.